

GENERAL DYNAMICS
European Land Systems

DURO 4x4

Wheeled Vehicles 



Durable and Robust
Military Tactical Vehicle

MANUFACTURER	GD European Land Systems-Mowag GmbH
PRODUCT	DURO
DRIVE MODE	4x4
CATEGORY	Military Tactical Vehicle
NUMBER OF SEATS	2+12



The DURO is a highly mobile all-terrain military tactical vehicle. The name DURO stands for DURable and ROBust. Even in the most difficult terrain, the DURO drives safely and reliably in every situation.

With its uniquely designed modular construction, the DURO can be modified in many configurations to accommodate a wide range of applications in a single vehicle.

Through the use of a variety of super-structures, the basic chassis cab is suitable for many missions. These include troop transporter, command and control, logistics or ambulance vehicle.

Product Features

WEIGHTS		ENGINE		BASELINE EQUIPMENT
Ready for operation	4.3 t	Manufacturer	FPT	Vehicle information system
Payload	2 t	Type	F1C	
Gross Vehicle Weight	6.3 t	Multi fuel capability	Yes	OPTIONAL EQUIPMENT
		No. of cylinders	4	Winch
DIMENSIONS		Performance	129 kW	Central Tire Inflation System (CTIS)
Overall length	6 m	Emission compliance	EURO III / VI	Preheat unit
Height	2.6 m	Torque	430 Nm	GPS
Overall width	2 m	TRANSMISSION		Runflat tires
Wheelbase	3.88 m	Manufacturer	ZF	Cab roof basket
Ground clearance	0.40 m	Type	8HP-90	Snow chains
Angle of approach	50°	Mode of operation	Automatic	Emission compliance EURO VI Engine
Angle of departure	32°	Number of gears	8	3rd seat in cab
Number of seats up to	14	DRIVELINE AND SUSPENSION		Trailer hitch
VEHICLE PERFORMANCE		Wheel drive	Permanent, four wheel	Trailer air brake system
Max Speed	100 km/h	Transfer case	One-speed with Torsen	Helicopter lifting devices
Gradient up to	70%	Differential	Torsen, self locking	Various shelter mission kits
Vertical obstacle	0.8 m	De-Dion axles with wheel hub gear, patented roll stabilizers		Air conditioning system
Turning circle diameter wall to wall	16 m	Brakes	Hydraulic disc type with ABS und ESP	
Fuel tank capacity	120 l	Steering	Hydraulically power assisted	
Range on hard level surface	700 km	Tires	275/80 R20 Optional 335/80 R20	
Power-to-weight ratio	20.48 kW/t			

Please note that the technical data refer to the baseline vehicle. They might vary due to configuration, version and mission.

GENERAL DYNAMICS
European Land Systems

The Transatlantic Partner for Land Defense in Europe

www.gdels.com

The Company reserves the right to modify details, design and building methods in order to comply with the latest technical innovations. All technical data are subject to change without notice.

© All company names and logos are copyright protected

GENERAL DYNAMICS
European Land Systems

General Dynamics
European Land Systems-Mowag GmbH
Unterseestrasse 65. 8280 Kreuzlingen, Switzerland
☎ +41 (0) 71 677 55 00
☎ +41 (0) 71 672 28 86
✉ info.wheeledvehicles@gdels.com